

Pizzato Elettrica S.r.l.
Via Torino, 1
36063 Marostica (VI)
ITALY

Tel. +39.0424.470.930
E-mail info@pizzato.com
Web www.pizzato.com

Article: **MK V11D49**
Description: Microswitch with red push button








Screw terminals **V** with plate

Housing:
Technopolymer housing

Protection degree:
IP00 without terminal cover
IP20 with terminal cover VF C01, VF C03
IP40 with terminal cover VF MKCx1x, VF C02


General data:
Ambient temperature: -25°C … +85°C
Max. actuation frequency: 3600 operating cycles/hour
Mechanical endurance: 10 million operating cycles
Safety parameters B_{10D}: 20,000,000 for NC contacts

Contact block characteristics:
1NO+1NC changeover
Mobile contact with single interruption and double contacts




Contacts with single interruption and double contacts


Positive contact opening in conformity with standards:
Device without positive opening. If installed individually, not suitable for safety applications



Actuation forces and travels:
Hand operated



Cable cross section (flexible copper strands):
min. 1 x 0,34 mm2 (1 x AWG 22)
max. 2 x 1,5 mm2 (2 x AWG 16)
Wire stripping length:
7 mm



Compliance with the requirements of:
Low Voltage Directive 2014/35/EU,
EMC Directive 2014/30/EU,
RoHS Directive 2011/65/EU.

Conformità alle norme:
IEC 60947-5-1, EN 60947-5-1, IEC 60529, EN 60529, EN 60947-1, IEC 60947-1, EN IEC 63000.
Approvals:
UL 508, CSA C22.2 No. 14, EN 60947-1, EN 60947-5-1

Device screw tightening torques:
Terminal screws: 0,6 ... 0,8 Nm
M4 fixing screws, body (insert washer): 0.8 … 1.2 Nm
Attention: A tightening torque higher than 1.2 Nm can cause the breaking of the microswitch.

Markings and quality marks:

Electrical data:

Thermal current (Ith): 16 A
Rated insulation voltage (Ui): 250 Vac 300 Vdc
Rated impulse withstand voltage (Uimp): 4 kV
Conditional short circuit current: 1000 A acc. to EN 60947-5-1
Protection against short circuits: type gG fuse 16 A 250 V
Pollution degree: 3
Dielectric strength 2000 Vac/min.

Utilization category:

Alternate current: AC15 (50...60 Hz)

Ue (V)	120	250
Ie (A)	3	5

Direct current: DC13

Ue (V)	24	125	250
Ie (A)	4	0,6	0,3

© 2019 Copyright Pizzato Elettrica. Technical modifications and errors reserved. The data quoted in this sheet are carefully checked and represent typical series values.
Descriptions of device and its applications, the control contexts, details on external controls, installation and operating information are given to the best of our knowledge. This does not mean however that any assured properties or other claims under liability law that extend beyond the "General Sales Terms" as stated in the Pizzato Elettrica general catalogue may be derived. The user is not absolved of his obligation to examine our information and recommendations before using them for his own purposes.

Pizzato Elettrica S.r.l.
Via Torino, 1
36063 Marostica (VI)
ITALY

Tel. +39.0424.470.930
E-mail info@pizzato.com
Web www.pizzato.com

Article: **MK V11D49**
Description: Microswitch with red push button


Characteristics approved by IMQ and CCC
Rated insulation voltage (Ui): 250 Vac
Conventional free air thermal current (Ith): 16 A
Protection against short circuits: type gG fuse 16 A 250 V
Rated impulse withstand voltage (Uimp): 4 kV
Conditional short circuit current: 1000 A
Protection degree of the housing: IP00
Terminals: screw terminals/faston
Pollution degree: 3
Utilization category: AC15
Operating voltage (Ue): 250 Vac (50 Hz)
Operating current (Ie): 5 A

Forms of the contact element: A; B; C
Positive opening of contacts on contact blocks: 1, 3
In conformity with standards: EN 60947-1, EN 60947-5-1, fundamental requirements of the Low Voltage Directive 2014/35/EU.


Characteristics approved by UL
Electrical Ratings:
Q300 pilot duty (69 VA, 125-250 V dc)
A300 pilot duty (720 VA, 120-300 V ac)

Mechanical stop

Acc. to EN ISO 14119 paragraph 5.2 "the position sensors must not be used as mechanical stop".




The actuator must not exceed the max. travel as indicated in the travel diagrams.



The guard must not use the switch head as a mechanical stop.

Lever with direct action (D) - Type 3

Vmax (m/s)	Vmin (mm/s)
0,03 x L	0,0166 x L



© 2019 Copyright Pizzato Elettrica. Technical modifications and errors reserved. The data quoted in this sheet are carefully checked and represent typical series values.
Descriptions of device and its applications, the control contexts, details on external controls, installation and operating information are given to the best of our knowledge. This does not mean however that any assured properties or other claims under liability law that extend beyond the "General Sales Terms" as stated in the Pizzato Elettrica general catalogue may be derived. The user is not absolved of his obligation to examine our information and recommendations before using them for his own purposes.

Pizzato Elettrica S.r.l.
Via Torino, 1
36063 Marostica (VI)
ITALY

Tel. +39.0424.470.930
E-mail info@pizzato.com
Web www.pizzato.com

This device **does not** feature positive opening and therefore **cannot be used individually for safety functions.**

© 2019 Copyright Pizzato Elettrica. Technical modifications and errors reserved. The data quoted in this sheet are carefully checked and represent typical series values.
Descriptions of device and its applications, the control contexts, details on external controls, installation and operating information are given to the best of our knowledge. This does not mean however that any assured properties or other claims under liability law that extend beyond the "General Sales Terms" as stated in the Pizzato Elettrica general catalogue may be derived. The user is not absolved of his obligation to examine our information and recommendations before using them for his own purposes.