



Figure similar

LOGO! 24RCE, logic module,display power supply / I/O: 24 V AC/24 V DC/relay, 8 DI/4 DO, memory 400 blocks, modularly expandable, Ethernet, integrated web server, data log, user-defined web pages, standard microSD card for LOGO! Soft Comfort V8.4 or higher, older projects executable cloud connection, MQTT in all LOGO! 8.4 basic units

Display	
with display	Yes
Installation type/mounting	
Mounting	on 35 mm DIN rail, 4 spacing units wide
Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Rated value (AC)	
• 24 V AC	Yes
Line frequency	
• permissible range, lower limit	47 Hz
• permissible range, upper limit	63 Hz
Time of day	
Time switching clocks	
• Number	400; Max. 400, function-specific
• Power reserve	480 h
Digital inputs	
Number of digital inputs	8
Digital outputs	
Number of digital outputs	4; Relays
Short-circuit protection	No; external fusing necessary
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	3 A
— with resistive load, max.	10 A
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class B, for use in residential areas	Yes; Radio interference suppression according to EN55011, Limit Value Class B
Standards, approvals, certificates	
Siemens Eco Profile (SEP)	Siemens EcoTech
CE mark	Yes
CSA approval	No; covered by UL cert

UL approval	Yes																																				
FM approval	Yes																																				
developed in accordance with IEC 61131	Yes																																				
according to VDE 0631	Yes																																				
Marine approval	Yes; in preparation																																				
Ecological footprint																																					
• environmental product declaration	Yes																																				
Global warming potential																																					
— global warming potential, (total) [CO2 eq]	51.5 kg																																				
— global warming potential, (during production) [CO2 eq]	9.64 kg																																				
— global warming potential, (during operation) [CO2 eq]	42.1 kg																																				
— global warming potential, (after end of life cycle) [CO2 eq]	-0.364 kg																																				
Ambient conditions																																					
Ambient temperature during operation																																					
• min.	-20 °C; No condensation																																				
• max.	55 °C																																				
Ambient temperature during storage/transportation																																					
• min.	-40 °C																																				
• max.	70 °C																																				
Altitude during operation relating to sea level																																					
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 080 hPa ... 795 hPa (-1 000 m ... +2 000 m)																																				
Dimensions																																					
Width	71.5 mm																																				
Height	90 mm																																				
Depth	60 mm																																				
Classifications																																					
	<table><tr><td></td><td>Version</td><td>Classification</td></tr><tr><td>eClass</td><td>14</td><td>27-24-22-16</td></tr><tr><td>eClass</td><td>12</td><td>27-24-22-16</td></tr><tr><td>eClass</td><td>9.1</td><td>27-24-22-16</td></tr><tr><td>eClass</td><td>9</td><td>27-24-22-16</td></tr><tr><td>eClass</td><td>8</td><td>27-24-22-16</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-22-16</td></tr><tr><td>eClass</td><td>6</td><td>27-24-22-16</td></tr><tr><td>ETIM</td><td>10</td><td>EC001417</td></tr><tr><td>ETIM</td><td>9</td><td>EC001417</td></tr><tr><td>ETIM</td><td>8</td><td>EC001417</td></tr><tr><td>ETIM</td><td>7</td><td>EC001417</td></tr></table>		Version	Classification	eClass	14	27-24-22-16	eClass	12	27-24-22-16	eClass	9.1	27-24-22-16	eClass	9	27-24-22-16	eClass	8	27-24-22-16	eClass	7.1	27-24-22-16	eClass	6	27-24-22-16	ETIM	10	EC001417	ETIM	9	EC001417	ETIM	8	EC001417	ETIM	7	EC001417
	Version	Classification																																			
eClass	14	27-24-22-16																																			
eClass	12	27-24-22-16																																			
eClass	9.1	27-24-22-16																																			
eClass	9	27-24-22-16																																			
eClass	8	27-24-22-16																																			
eClass	7.1	27-24-22-16																																			
eClass	6	27-24-22-16																																			
ETIM	10	EC001417																																			
ETIM	9	EC001417																																			
ETIM	8	EC001417																																			
ETIM	7	EC001417																																			
Approvals / Certificates																																					
General Product Approval																																					
 EG-Konf.	 Manufacturer Declaration	 UL	 RCM	KC																																	
For use in hazardous locations		Maritime application																																			
 CQC	 UL	FM	 ABS	 BUREAU VERITAS	 DNV																																
Maritime application			Environment																																		



[NK / Nippon Kaiji Kyokai](#)

[CCS \(China Classification Society\)](#)



last modified:

5/16/2025