AUTOMAX

NXT SOUNDER
NXT SOUNDER NFC



50 mm


NXT SOUNDER
NXT SOUNDER NFC

kg
0,04

IP69K

94 dB max

Module SILVER



SIRENA

NXT SOUNDER and NXT SOUNDER NFC are the piezoelectric acoustic modules of the NXT stack light.
NXT SOUNDER: 3 intermittent sounds with 12V and 24V bases and 1 intermittent sound with 110/240V base.
NXT SOUNDER NFC controls 3 sounds that can be selected from 12 available in MySirena App.

GENERAL FEATURES
Operating temperature: -40° +60°C
IP rating: IP66, IP69K
Impact resistance: IK08
Continuous operation
Insulation class II

MECHANICAL FEATURES
Self-extinguishing polycarbonate with high impact resistance (IK08), suitable for outdoor use thanks to the IP66-IP69K protection rating, guaranteed by the EPDM gasket on each module.

ACOUSTIC FEATURES
NXT SOUNDER: Piezoelectric unit, producing 3 intermittent sounds (with 12V and 24V bases) - frequencies 2930/3050Hz | dB 87÷94 and 1 intermittent sound (with 110/240V base) - frequency 3050Hz
NXT SOUNDER NFC: Piezoelectric unit, producing 3 sounds that can be selected from 12 available in MySirena App - mixed frequencies | dB 73÷92.

CERTIFICATIONS
CE UKCA · UL PENDING · NFC RED-compliant device

NXT SOUNDER

V DC	12	24	-	-	-	-
V AC	-	-	12	24	110	240
mA	17	27	30	49	14	10
dB(A)1m	85	91	88	94	91	91

NXT SOUNDER NFC

V DC	24	-
V AC	-	24
mA	10	17
dB(A)1m	90	92

				SILVER
NXT SOUNDER	○ 33928	● 33930	○ 33937	● 33998
NXT SOUNDER NFC 24V ACDC	○ 33929	● 33935	○ 33938	● 33997

NXT | PRE-ASSEMBLED STACK LIGHTS



NXT WM LT + 3LM GRE/AMB/RED + SOUNDER + BS

24V ACDC

○ 33990



OTHER CONFIGURATIONS AVAILABLE ON REQUEST

sirena.it